

Logix PakStrapper TP-601D1

Automatic Strapping Machine

Standard Performance

DOVERCO
Strategic. Packaging.

Accurate Electronic Tension Control

The Accurate Automatic Strapping Machine

The Logix PakStrapper Standard Performance machine features high speed, efficient sealing and accurate tension to deliver professional strapping performance.




PU Casters
2 free and 2 with brake



Accurate Strap Tension

Strap tension can be adjusted accurately by a simple turn of the dial to get an optimal package.



Multiple Methods of Cycle Initiation

The machine can be operated by photo eye switch, foot pedal switch, and start switch.



Auto Strap Feeding

Friendly design to feed the strap automatically without the need to access the inside of the machine.



ITEM NUMBER	D171347
PP STRAPPING	9 mm - 8" core
TENSION RANGE	7 - 45 kg
ELECTRICAL	110V 1-PHASE
TABLE HEIGHT	810 mm (31.9")
ARCH (W x H)	850 x 600 mm (33.4" x 23.6")
MAX PRODUCT HEIGHT	546 mm (21.5")



Auto Strap Refeed

The machine will automatically refeed the strap if a mis-feed occurs.



Auto Strap Ejector

Loop-ejector clears unwanted strap automatically if the machine is activated without a package.



Robust & Compact Strapping Head

Robust mechanism designed to ensure excellent durability of the machine.

Up To
29 CYCLES
PER MINUTE